

tyco | Cloud

Simplify Security with Illustra Cloud Cameras



Simplify Security with Tyco Cloud

Introducing Tyco Cloud, a cloud-based physical security management suite from Johnson Controls developed for video surveillance, access control, intelligence, and integration services on an open and modern microservices architecture. Tyco Cloud provides the cost-efficiency of software as a service (SaaS) with the simplicity of secure cloud connected hardware.

Since its inception, Tyco Cloud has helped customers store and manage over 25 billion minutes of video surveillance in the cloud and is available in 140 countries and 50+ data centers worldwide and growing.

Illustra Cloud Cameras 3MP & 8MP Mini-Domes



Key Features

- Stores video in the camera, in the cloud, or both as needed
- Integrates with Tyco Cloud video management software
- Cold storage for cost-effective and secure video archiving
- IK10-rated vandal resistance and IP68-rated protection against dust and water damage
- P-iris for image clarity in changing light conditions
- Motion detection for instant intruder alerts

Tyco Cloud lets businesses easily scale and streamline security operations by moving costly and complex system infrastructure to the cloud for simplified management.

Simplify Surveillance in the Cloud

Reduce complex surveillance installation and video management costs with Illustra Cloud Cameras. This flexible alternative to traditional IP cameras provides the option for storing video on-site, in the cloud, or both. The easy to use interface can be accessed from a web-based platform or mobile device and activated in minutes, maximizing uptime and accelerating training. These cameras are ideal for a variety of industries ranging from building management and finance to retail, education, and smart cities.

High-Quality, Versatile Video Streaming to the Cloud

The powerful Illustra Cloud Mini-Dome Cameras are designed to offer a high-image quality, feature rich surveillance option for a wide range of applications. The increased amount of pixels per foot on the 8MP model improves image detail in wide areas such as loading docks

and airport terminals. Also, the Mini-Domes feature built-in IR illuminators to produce clear images at an effective distance in a variety of low light conditions. Deployments that strive for a combination of high-resolution and high-performance at a competitive price point, all while simplifying installation and configuration stand to benefit the most from the these Illustra Cloud Cameras.

Enhance Visibility with Efficient Management Tools

Time-saving, productivity-boosting tools are uniquely bundled into Tyco Cloud Camera video management software. View and scan through 24 hours of recorded video and events from up to 100 cameras at the same time in only 60 seconds with Hyper View. Supervise user roles and permissions, system support, services, and troubleshooting from the centralized Enterprise Manager. This feature includes SMS alerts and a map view for quickly addressing issues remotely.


Safeguard Against Cyber Attacks Across Devices

Illustra Cloud Cameras have been designed to be resilient against cyber-threats. Our Cloud products are gated, analyzed, tested and required to meet or exceed the rigorous standards of the Johnson Controls Cyber Solutions Product Security Program for every consecutive release. This holistic approach is aimed at providing peace of mind to our customers. Our security mindset begins at initial design concept and is supported through deployment, including a rapid incident response to meet the comprehensive and evolving cybersecurity environments.

Specifications

Operational	3MP	8MP
Video Compression	H.264 / H.265 / MJPEG	
Max Frame Rate	3MP @ 30 fps	8MP @ 15 fps
Resolution & Aspect Ratio	2048x1536 (QXGA) 4:3	3840x2160 (4K) 16:9
	1920x1080 (1080p) 16:9	3264x1840 16:9
	1664x936 16:9	2592x1944 4:3
	1280x720 (720p) 16:9	2688x1520 16:9
	1024x576 (PAL+) 16:9	2048x1536 (QXGA) 4:3
	640x360 (nHD) 16:9	1920x1080 (1080p) 16:9
Video Streams	480x360 (480) 16:9	1280x960 (SXGA-) 4:3
	384x288 4:3	1280x720 (720p) 16:9
		800x600 (SVGA) 4:3
		640x480 (640VGA) 4:3
		640x360 (nHD) 16:9
Video Streams	Triple Streaming with a Maximum of 5 Concurrent Streams	
Imager	Progress Scan RGB CMOS 1/2.8"	Progress Scan RGB CMOS 1/2.5"
Image Orientation Settings	Flip, Mirror	
Lens Type	Motorized Varifocal and Focus, P-iris control, IR corrective	
Focus Control	Motorized, Auto Focus	
Focal Length	2.8-12mm	3.4-9mm
Field of View Wide (H/V)	98°/71°	104°/56°
Field of View Telephoto (H/V)	35°/26°	42°/24°
Aperture	F/1.4 (W) F/2.7 (T)	F/1.5 (W) F/2.9 (T)
Minimum Illumination		
Color, 1/4s, 30 IRE, AGC	0.03 Lux	0.03 Lux
B/W, 1/4s, 30 IRE, AGC	0.001 Lux	0.0003 Lux
w/ IR	0.0 Lux	0.0 Lux
IR Distance	82ft (25m)	

Dynamic Range	Triple Exposure, True WDR 120 dB Technologies	Triple Exposure, True WDR 100 dB Technologies
Day/Night	True Day/Night with ICR	
Shutter Speed	1/4 - 1/10,000 sec	
ONVIF-Compliant	Profile 2	
Motion Detection Zones	3	
Alarms I/O	1/1	
Analog Video Output	Yes	
Audio	1/1	
Simultaneous Users	5	
Languages	English, French, Italian, German, Spanish	
Network		
Ethernet Interface	IEEE 802.3, 10/100Base-T Ethernet, Female RJ45, Auto-Negotiation	
Supported Protocols	TCP/IP, IPv4, IPv6, TCP, UDP, HTTP, FTP, DHCP, WS-Discovery, DNS, DDNS, RTP, RTCP, RTSP, TLS, Unicast, Multicast, NTP, ICMP, IGMP, SMTP, WS-Security, IEEE 802.1x, PEAP, EAP-TLS, EAPoL, SSH, HTTPS, SOAP, WSAddressing, CIFS, SNMP, UPNP, RTSP, LLDP	
Configuration Management		
Web Browsers	Internet Explorer 8.0 or above, Firefox, Safari, Chrome	
Security	TLS - RFC5246 v1.2, HTTPS (HTTP over TLS) - RFC2818, WS-Security, Certificate Management, Multi-Level Password Protection, IP Address, Filtering, HTTPS Encryption, One-Click Security Hardening, User Access Log, Validate Complex Credentials, Disabling Unused Protocols, IEEE, 802.1x Including: PEAP, EAP-TLS, EAPoL	
Onboard Storage		
Card Support	Western Digital Purple SD with Realtime Health Monitoring	
Pre-Alarm Recording	10 seconds	
Recording Format	MKV (encrypted)	
Playback	Via Tyco Cloud website or mobile app	
Recording Trigger	Motion detection or recording schedule	
Scheduled Uploading	Yes	
Cloud Storage		
Scheduled/24x7	Record to cloud on any schedule at any resolution or bitrate	
Motion Only	Record to cloud only when motion is detected	
Bookmarks Only	Record to cloud only bookmarked video and share securely	
Cold Storage	Cost effective recording of archival video 6 months or longer	
Electrical		
Power Input	Power over Ethernet (PoE) IEEE 802.3af Type 1 Class 3; 24 VAC	
Power Draw	12W	
Physical		
Dimensions (RxH)	Ø4.8 x 4.2 in (Ø123 x 107 mm)	
Housing Color	2.14lbs (0.97kg)	
Operating Temperature	-58°F to 122°F (-50°C to 50°C) Extended Temperature: 140°F (60°C) for 5 hours a day with IR illuminators OFF ¹	
Humidity	Up to 90% non-condensing	
Vandal Resistant	IK10	
Outdoor Rating	IP67	
Regulatory		
Safety	EN60950-1; CAN/CSA-C22.2 No. 60950-1	
Emissions	FCC Part 15 Class A; EN55032 Class A; AS/NZS CISPR 32 Class A; ICES-003/NMB-003 Class A	
Immunity	EN55024, EN50130-4	
Environment	RoHS; WEEE	



Ordering Information

Model	Description
TCCFS03D02XXX	3MP Indoor/Outdoor Dome IR 2.8-12mm. 32GB-512GB Internal Storage
TCCFS08D04XXX	8MP Indoor/Outdoor Dome IR 3.4-9mm. 32GB-512GB Internal Storage

Accessories

Model	Description
IFDRECMNT	Recessed Mount for Flex Mini-Domes (IFXX Series)
IFMDBWSMK	Illustra Flex Mini-Dome Smoked Vandal Bubble Assembly
ADC16MPCAPIW	Illustra compact mini-dome pendant cap, white, 3/4" NPT
ADLOMARM	Gooseneck Arm (White)
ADCDMCRNRO	Outside Corner Mount Adaptor (White)
ADCDMPOLE	Pole Mount Adaptor (White)

Accessories

Accessory Type	Image	Model Number	Description	Dimensions	Color
Mount		IFDRECMNT	Mini-Dome recessed mount	Ø7.76 x 1.61 in (Ø197 x 41 mm)	RAL 9003 Signal White
Bubble		IFMDBWSMK	Smoked bubble for use with Flex Mini-Domes	Ø4.8 x 4.2 in (Ø123 x 107 mm)	RAL 9003 Signal White (Trim)
Pendant Cap		ADC16MPCAPIW	Pendant Cap: Indoor/Outdoor, White/Black	Ø5.8 x 2.2 x 5.8 in (Ø148 x 55 x 147.4 mm)	RAL 9003 Signal White RAL 9017 Traffic Black
Gooseneck Arm		ADLOMARM	For use with Pendant Cap	4.4 x 8.78 x 4.4 in (112.5 x 222.9 x 112.5 mm)	RAL 9003 Signal White RAL 9017 Traffic Black
Outside Corner Mount Adapter		ADCDMCRNRO	For use with Pendant Cap and Gooseneck Arm, or directly to the camera back plate.	5.18 x 7.58 in (131.5 x 192.5 mm)	RAL 9003 Signal White
Pole Mount Adapter		ADCDMPOLE	For use with Pendant Cap and Gooseneck Arm, or directly to the camera back plate.	Wraps around pole	RAL 9003 Signal White

Illustra Cloud Cameras 3MP Bullet

3MP Bullet



Key Features

- Stores video in the camera, in the cloud, or both as needed
- Integrates with Tyco Cloud video management software
- Cold storage for cost-effective and secure video archiving
- IK10-rated vandal resistance and IP68-rated protection against dust and water damage
- P-iris for image clarity in changing light conditions
- Motion detection for instant intruder alerts

Tyco Cloud lets businesses easily scale and streamline security operations by moving costly and complex system infrastructure to the cloud for simplified management.

Simplify Surveillance in the Cloud

Reduce complex surveillance installation and video management costs with Illustra Cloud Cameras. This flexible alternative to traditional IP cameras provides the option for storing video on-site, in the cloud, or both. The easy to use interface can be accessed from a web-based platform or mobile device and activated in minutes, maximizing uptime and accelerating training. These cameras are ideal for a variety of industries ranging from building management and finance to retail, education, and smart cities.

A Tough Exterior with Cloud Capabilities

Solid yet affordable, the Illustra Cloud 3MP Bullet Camera is ideal for both interior and exterior applications that require a vandal- and weather-resistant option. The Cloud

Bullet Camera comes complete with built-in IR illuminators for clear video images in extreme low light or zero illumination conditions providing crisp, clear video quality both day and night.

Enhance Visibility with Efficient Management Tools

Time-saving, productivity-boosting tools are uniquely bundled into Tyco Cloud Camera video management software. View and scan through 24 hours of recorded video and events from up to 100 cameras at the same time in only 60 seconds with Hyper View. Supervise user roles and permissions, system support, services, and troubleshooting from the centralized Enterprise Manager. This feature includes SMS alerts and a map view for quickly addressing issues remotely.


Safeguard Against Cyber Attacks Across Devices

Illustra Cloud Cameras have been designed to be resilient against cyber-threats. Our Cloud products are gated, analyzed, tested and required to meet or exceed the rigorous standards of the Johnson Controls Cyber Solutions Product Security Program for every consecutive release. This holistic approach is aimed at providing peace of mind to our customers. Our security mindset begins at initial design concept and is supported through deployment, including a rapid incident response to meet the comprehensive and evolving cybersecurity environments.


Specifications

Operational		
Video Compression	H.264 / H.265 / MJPEG	
Max Frame Rate	30ips @ 3MP, 60ips @ 1080p	
Resolution & Aspect Ratio	2048x1536 (QXGA) 4:3	1024x576 (PAL+) 16:9
	1920x1080 (1080p) 16:9	640x360 (nHD) 16:9
	1664x936 16:9	480x360 (480) 4:3
	1280x720 (720p) 16:9	384x288 4:3
Video Streams	Progressive Scan RGB 1/2.8" CMOS	
Imager	Triple Streams	
Image Orientation Settings	Flip and Mirror	
Lens Type	Motorized Varifocal and Focus, P-iris control, IR corrective	
Focus Control	Motorized	
Focal Length	2.8-12mm	
Field of View Wide (H/V)	98°/71°	
Field of View Telephoto (H/V)	35°/26°	
Aperture	F/1.4 (W)	
	F/2.7 (T)	
Minimum Illumination		
Color, 1/4s, 30 IRE, AGC	0.03 Lux	
B/W, 1/4s, 30 IRE, AGC	0.001 Lux	
w/ IR	0.0 Lux	
IR Distance	82ft (25m)	
Dynamic Range	Triple Exposure, True WDR 120 dB Technologies	
Day/Night	True Day/Night with ICR	
Shutter Speed	1/4-1/10000	
ONVIF-Compliant	Profile S	
Motion Detection Zones	3	
Analog Video Output	Yes	
Audio	1/1	
Simultaneous Users	5	
Languages	English, French, Italian, German, Spanish	

Network	
Ethernet Interface	10/100Base-T, RJ-45
Supported Protocols	TCP/IP, IPv4, IPv6, TCP, UDP, HTTP, FTP, DHCP, WS-Discovery, DNS, DDNS, RTP, RTCP, TLS, Unicast, Multicast, NTP, SMTP, WS-Security, IEEE 802.1x, PEAP, SSH, HTTPS, SOAP, WS-Addressing, CIFS, SNMP, UPNP, RTSP, LLDP
Configuration Management	
Web Browsers	IE9 and above, Firefox, Chrome, Safari
Security	Multiple user access levels, IP address filtering, user access log, IEEE 802.1x
Onboard Storage	
Card Support	Western Digital Purple SD with Realtime Health Monitoring
Pre-Alarm Recording	10 seconds
Recording Format	MKV (encrypted)
Playback	Via Tyco Cloud website or mobile app
Recording Trigger	Motion detection or recording schedule
Scheduled Uploading	Yes
Cloud Storage	
Scheduled/24x7	Record to cloud on any schedule at any resolution or bitrate
Motion Only	Record to cloud only when motion is detected
Bookmarks Only	Record to cloud only bookmarked video and share securely
Cold Storage	Cost effective recording of archival video 6 months or longer
Electrical	
Power Input	Power over Ethernet (PoE) IEEE 802.2af Type 1 Class 3; 24 VAC
Power Draw	15W
Physical	
Dimensions (RxH)	Ø3.05 x 9.25 in (Ø77.5 x 235 mm)
Weight	2.65lbs (1.2kg)
Housing Color	Signal White Pantone RAL 9003
Operating Temperature	-40°F to 122°F (-40°C to 50°C)
Humidity	Up to 90% non-condensing
Vandal Resistant	IK10
Outdoor Rating	IP68
Regulatory	
Safety	EN60950-1; IEC60950-1; CSA 22.2 No. 60950
Emissions	FCC Part 15 Class A; EN55032 Class A; AS/NZS; CISPR 32 Class A; ICES-003/NMB-003 Class A
Immunity	EN55024, EN50130-4
Environment	RoHS; WEEE



Accessories

Accessory Type	Image	Model Number	Description	Dimensions	Color
Mount		IFBMNTBOX	Mounting adapter for connecting bullet camera to wall.	Ø6 x 2.5 in (Ø147 x 60 mm)	RAL 9003 Signal White

Ordering Information

Model	Description
TCCFS03B03XXX	3MP Indoor/Outdoor Bullet IR 2.8-12mm. 32GB-512GB Internal Storage

Accessories

Model	Description
IFBMNTBOX	Flex Bullet Mounting Box (IFXX Series)

3MP Compact Mini-Dome

Illustra Cloud Cameras 3MP Compact Mini-Dome



Key Features

- Stores video in the camera, in the cloud, or both as needed
- Integrates with Tyco Cloud video management software
- Cold storage for cost-effective and secure video archiving
- IK10-rated vandal resistance and IP67-rated protection against dust and water damage
- P-iris for image clarity in changing light conditions
- Motion detection for instant intruder alerts

Tyco Cloud lets businesses easily scale and streamline security operations by moving costly and complex system infrastructure to the cloud for simplified management.

Simplify Surveillance in the Cloud

Tyco Cloud lets businesses easily scale and streamline security operations by moving costly and complex system infrastructure to the cloud for simplified management. Reduce complex surveillance installation and video management costs with Illustra Cloud Cameras. This flexible alternative to traditional IP cameras provides the option for storing video on-site, in the cloud, or both. The easy to use interface can be accessed from a web-based platform or mobile device and activated in minutes, maximizing uptime and accelerating training. These cameras are ideal for a variety of industries ranging from building management and finance to retail, education, and smart cities.

Versatile and Feature-Rich Cloud Cameras

With a small, aesthetically pleasing design, the affordably priced Illustra 3MP & 8MP Cloud Mini-Dome Cameras offer an effective solution for retail stores, schools, bank branches and small to medium size offices. A P-Iris lens delivers clear video in changing light while built-in IR illuminators produce clear images at an effective distance in a variety of low light conditions. With a recessed mounting option, these cameras can be strategically placed to blend into a variety of both interior and exterior locations.

Enhance Visibility with Efficient Management Tools

Time-saving, productivity-boosting tools are uniquely bundled into Tyco Cloud Camera video management software. View and scan through 24 hours of recorded video and events from up to 100 cameras at the same time in only 60 seconds with Hyper View. Supervise user roles and permissions, system support, services, and troubleshooting from the centralized Enterprise Manager. This feature includes SMS alerts and a map view for quickly addressing issues remotely.


Safeguard Against Cyber Attacks Across Devices

Illustra Cloud Cameras have been designed to be resilient against cyber-threats. Our Cloud products are gated, analyzed, tested and required to meet or exceed the rigorous standards of the Johnson Controls Cyber Solutions Product Security Program for every consecutive release. This holistic approach is aimed at providing peace of mind to our customers. Our security mindset begins at initial design concept and is supported through deployment, including a rapid incident response to meet the comprehensive and evolving cybersecurity environments.





Specifications

Operational									
Video Compression	H.264 / H.265 / MJPEG								
Max Frame Rate	30ips @ 3MP, 60ips @ 1080p								
Resolution & Aspect Ratio	<table border="0"> <tr> <td>2048x1536 (QXGA) 4:3</td> <td>1024x576 (PAL+) 16:9</td> </tr> <tr> <td>1920x1080 (1080p) 16:9</td> <td>640x360 (nHD) 16:9</td> </tr> <tr> <td>1664x936 16:9</td> <td>480x360 (480) 4:3</td> </tr> <tr> <td>1280x720 (720p) 16:9</td> <td>384x288 4:3</td> </tr> </table>	2048x1536 (QXGA) 4:3	1024x576 (PAL+) 16:9	1920x1080 (1080p) 16:9	640x360 (nHD) 16:9	1664x936 16:9	480x360 (480) 4:3	1280x720 (720p) 16:9	384x288 4:3
2048x1536 (QXGA) 4:3	1024x576 (PAL+) 16:9								
1920x1080 (1080p) 16:9	640x360 (nHD) 16:9								
1664x936 16:9	480x360 (480) 4:3								
1280x720 (720p) 16:9	384x288 4:3								
Video Streams	Triple Streams								
Imager	Progressive Scan RGB 1/2.8" CMOS								
Image Orientation Settings	Flip and Mirror								
Lens Type	Fixed								
Focus Control	Fixed								
Focal Length	2.9mm								
Field of View Wide (H/V)	102°/77°								
Aperture	F1.8								
Minimum Illumination	0.01 Lux								
Dynamic Range	Triple Exposure, True WDR 120 dB Technologies								
Day/Night	Soft Day/Night								
Shutter Speed	1/4 - 1/10,000 sec								
ONVIF-Compliant	Profile S								
Motion Detection Zones	3								
Simultaneous Users	5								
Languages	English, French, Italian, German, Spanish								

Network	
Ethernet Interface	10/100Base-T, RJ-45
Supported Protocols	TCP/IP, IPv4, IPv6, TCP, UDP, HTTP, FTP, DHCP, WS-Discovery, DNS, DDNS, RTP, RTCP, RTSP, TLS, Unicast, Multicast, NTP, ICMP, IGMP, SMTP, WS-Security, IEEE 802.1x, PEAP, EAP-TLS, EAPoL, SSH, HTTPS, SOAP, WSAddressing, CIFS, SNMP, UPNP, RTSP, LLDP
Configuration Management	
Web Browsers	Internet Explorer 8.0 or above, Firefox, Safari, Chrome
Security	One-Click Security Hardening, User Access Log, Validate Complex Credentials, Disabling Unused Protocols IEEE 802.1x including: PEAP, EAP-TLS, EAPoL
Onboard Storage	
Card Support	Western Digital Purple SD with Realtime Health Monitoring
Pre-Alarm Recording	10 seconds
Recording Format	MKV (encrypted)
Playback	Via Tyco Cloud website or mobile app
Recording Trigger	Motion detection or recording schedule
Scheduled Uploading	Yes
Cloud Storage	
Scheduled/24x7	Record to cloud on any schedule at any resolution or bitrate
Motion Only	Record to cloud only when motion is detected
Bookmarks Only	Record to cloud only bookmarked video and share securely
Cold Storage	Cost effective recording of archival video 6 months or longer
Electrical	
Power Input	Power over Ethernet (PoE) IEEE 802.3af Type 1 Class 2
Power Draw	6W
Physical	
Dimensions (RxH)	4.3 x 2in (110 x 52mm)
Weight	1.1lbs (0.5kg)
Housing Color	Signal White Pantone RAL 9003
Operating Temperature	-40°F to 122°F (-40°C to 50°C)
Humidity	Up to 90% non-condensing
Vandal Resistant	IK10
Outdoor Rating	IP67
Regulatory	
Safety	EN60950-1; IEC 60950-1; CSA 22.2 No. 60950
Emissions	FCC Part 15 Class A; EN55032 Class A; AS/NZS CISPR 32 Class A; ICES-003/NMB-003 Class A
Immunity	EN55024; EN50130-4
Environment	RoHS; WEEE



Accessories

Accessory Type	Image	Model Number	Description	Dimensions	Color
Pendant Cap		ADC16MPCAPIW	Pendant Cap: Indoor/Outdoor, White/Black	Ø5.8 x 2.2 x 5.8 in (Ø148 x 55 x 147.4 mm)	RAL 9003 Signal White RAL 9017 Traffic Black
Gooseneck Arm		ADLOMARM	For use with Pendant Cap	4.4 x 8.78 x 4.4 in (112.5 x 222.9 x 112.5 mm)	RAL 9003 Signal White RAL 9017 Traffic Black
Outside Corner Mount Adapter		ADCDMCRNRO	For use with Pendant Cap and Gooseneck Arm, or directly to the camera back plate.	5.18 x 7.58 in (131.5 x 192.5 mm)	RAL 9003 Signal White
Pole Mount Adapter		ADCDMPOLE	For use with Pendant Cap and Gooseneck Arm, or directly to the camera back plate.	Wraps around pole	RAL 9003 Signal White

Ordering Information

Model	Description
TCCFS03C01XXX	3MP Indoor/Outdoor Dome No IR 2.8mm. 32GB-512GB Internal Storage

Accessories

Model	Description
ADC16MPCAPIW	ADC16MPCAPIW Illustra compact mini-dome pendant cap, white, 3/4" NPT
ADLOMARM	Gooseneck Arm (White)
ADCDMCRNRO	Outside Corner Mount Adaptor (White)
ADCDMPOLE	Pole Mount Adaptor (White)

Illustra Cloud Cameras 2MP IR PTZ



2MP IR PTZ

Key Features

- Stores video in the camera, in the cloud, or both as needed
- Integrates with Tyco Cloud video management software
- Cold storage for cost-effective and secure video archiving
- IK10-rated vandal resistance and IP67-rated protection against dust and water damage
- P-iris for image clarity in changing light conditions
- Motion detection for instant intruder alerts

Tyco Cloud lets businesses easily scale and streamline security operations by moving costly and complex system infrastructure to the cloud for simplified management.

Simplify Surveillance in the Cloud

Reduce complex surveillance installation and video management costs with Illustra Cloud Cameras. This flexible alternative to traditional IP cameras provides the option for storing video on-site, in the cloud, or both. The easy to use interface can be accessed from a web-based platform or mobile device and activated in minutes, maximizing uptime and accelerating training. These cameras are ideal for a variety of industries ranging from building management and finance to retail, education, and smart cities.


Manage Vast Surveillance Areas while Streaming to the Cloud

The Illustra Cloud IR PTZ is ideal for applications that require reliable, expansive functionality at an economical price point. With its 30x optical and 12x digital magnification, the IR PTZ is capable of effectively managing video quality at a distance of up to 1,000ft (300m).

Specifications

Operational		
Video Compression	H.264 / H.265 / MJPEG	
Max Frame Rate	60ips @ 2MP	
Resolution & Aspect Ratio	1920x1080 (1080p) 16:9	1800x450 16:9
	1600x900 (HD+) 16:9	640x360 (nHD) 16:9
	1280x720 (720p) 16:9	480x270 16:9
	1024x576 (PAL+) 16:9	320x180 16:9
	960x540 (qHD) 16:9	160x90 16:9
Video Streams	Triple Streaming	
Imager	Progress Scan RGB CMOS 1/3"	
Image Orientation Settings	Auto Flip	
Lens Type	IR Optical Corrective, Motorized Varifocal	
Focus Control	Motorized, Auto Focus	
Focal Length	4.3 - 129mm	
Field of View Wide (H/V)	65°/38°	
Field of View Telephoto (H/V)	2.4°/1.4°	
Aperture	F/1.6 (W)	
	F/4.7 (T)	
Minimum Illumination		
Color, 1/4s, 30 IRE, AGC	0.03 Lux	
B/W, 1/4s, 30 IRE, AGC	0.001 Lux	
w/ IR	0.0 Lux	
IR Distance	500ft (150m)	
Dynamic Range	Dual Exposure, True WDR 93 dB Technologies	
Day/Night	True Day/Night with ICR	
Shutter Speed	1/30(25) - 1/30,000 sec	
ONVIF-Compliant	Profile S	
Motion Detection Zones	1	
Blur Detection	Yes	
Alarms I/O	2/2	
Analog Video Output	NTSC/PAL Composite Video	
Audio	Bi-Directional 1/1	
Simultaneous Users	10	
Languages	English, French, Italian, German, Spanish	
PTZ Operations		
Optical Zoom	30x Optical Zoom, 12x Digital Zoom	
Pan Travel	360° Continuous	
Tilt Travel	-15° - +90°	
Manual Continuous Speed	0.1° - 90°/s	
Preset Accuracy	0.1°	
Preset Speed	Pan Speed: 0.1°/s - 240°/s	
	Tilt Speed: 0.1° - 160°/s	
Presets	Up to 16, each with 16 steps (presets)	
Sequences	17 Available, 16 Programmable	
Home Function	Preset, Pattern, Sequence, or Scan	
Auto Flip	Yes	
Noise Reduction	Digital Noise Reduction 2D and 3D	

Network	
Ethernet Interface	IE 9 or above, Firefox, Chrome, Safari
Supported Protocols	HTTPS, TLS, WS-Security, Certificate Management, Multi-Level Password Protection, IP address filtering, HTTPS encryption, One-Click Security Hardening, User Access Log, Validate Complex Credentials, Disabling Unused Protocols, IEEE 802.1x including: PEAP, EAP-TLS, EAPoL
Configuration Management	
Web Browsers	IE9 and above, Firefox, Chrome, Safari
Security	Multiple user access levels, IP address filtering, user access log, IEEE 802.1x
Onboard Storage	
Card Support	Western Digital Purple SD with Realtime Health Monitoring
Pre-Alarm Recording	10s
Recording Format	MKV (encrypted)
Playback	Via Tyco Cloud website or mobile app
Recording Trigger	Motion detection or recording schedule
Scheduled Uploading	Yes
Cloud Storage	
Scheduled/24x7	Record to cloud on any schedule at any resolution or bitrate
Motion Only	Record to cloud only when motion is detected
Bookmarks Only	Record to cloud only bookmarked video and share securely
Cold Storage	Cost effective recording of archival video 6 months or longer
Electrical	
Power Input	UPoE 802.3bt Class 6, 24VAC
Power Draw	51W
Physical	
Dimensions (RxH)	Ø 7.5in (190mm) Body Height: 11.9in (301mm) Height to Pedant Top: 13in (330mm) Ball: 6.3in (Ø160mm)
Weight	11.5lbs (5.2kg)
Housing Color	Signal White Pantone RAL 9003
Operating Temperature	-40°F to 122°F (-40°C to 50°C)
Storage Temperature	-40°F to 140°F (-40°C to 60°C)
Humidity	Up to 90% Non-Condensing
Vandal Resistant	IK10
Outdoor Rating	IP66
Regulatory	
Safety	CAN/CSA-C22.2 No. 60950-1; EN 60950-1
Emissions	FCC Part 15 Class A; CE EN55032 Class A; AS/NZS CISPR 22 Class A; ICES-003/NMB-003 Class A
Immunity	EN55024; EN50130-4
Environment	RoHS; WEEE



Accessories

Accessory Type	Image	Model Number	Description	Dimensions	Color
Recessed Mount		IFIRPTZWRECMT	Recessed mount for indoor or outdoor IR PTZ	Ø10.9 x 6.5 in (Ø276 x 166.1 mm)	RAL 9003 Signal White (Trim)
Ceiling Mount		IFIRPTZC2X2	Ceiling Mount Adapter Tile for use with IFIRPTZWRECMT	23.8 x 23.8 in (605 x 605 mm)	SHERWIN WILLIAMS 3HWT2-9002
Wall Mount		RHOSW	Short wall mount with end cap. For use with RHOWPA pole strap adapter and RHOWCA corner bracket adapter	With Dome Installed 14 x 9 x 11 in (366 x 218 x 282 mm)	RAL 9003 Signal White
Wall Mountt		RHOLW	Long wall mount with end cap	With Dome Installed 14 x 9 x 23 in (366 x 218 x 587 mm)	RAL 9003 Signal White
Over the Roof Mount		RHOTR	Affixes directly to vertical roof wall or parapet, positions dome away from wall	43 x 10 x 19 in (1098 x 243 x 473 mm)	RAL 9003 Signal White
Over the Roof Floor Mount		ROTRF	Enables RHOTR over-theroof mount to be installed on horizontal and vertical roof/parapet surfaces	15 x 10 x 10 in (369 x 240 x 240 mm)	RAL 9003 Signal White
Corner Bracket Adapter		RHOWCA	Enables long and short wall mounts (RHOSW and RHOLW) to affix to outside corners	7 x 8 x 5 in (185 x 210 x 125 mm)	RAL 9003 Signal White

Pole Strap Adapter		RHOWPA	Enables RHOSW and RHOLW to affix to outdoor corners	Straps Support: 5 x 3 x 1 in (138 x 79 x 27 mm) Pole Diameter: 2 to 38 in (53 to 951 mm)	RAL 9003 Signal White
Indoor Pendant Mount		RHOPN	Allows an outdoor dome housing to be suspended from an outdoor ceiling or horizontal surface	4.5 x 5 x 5 in (115 x 120 x 120 mm)	RAL 9003 Signal White
End Cap Assembly		ROENDC	Indoor/outdoor head adapter mount	3 x 4 x 8 in (64 x 103 x 194 mm)	RAL 9003 Signal White

Ordering Information

Model	Description
TCCFS02P05XXX	2MP Indoor/Outdoor PTZ No IR 30X Zoom. 32GB-512GB Internal Storage

Accessories

Model	Description
IFIRPTZWRECMT	Illustra Flex IR 30x PTZ indoor / outdoor recessed mount
IFIRPTZC2X2	Illustra Flex IR 30x PTZ 2X2 Ceiling Mount Adapter Plate
RHOSW	illustra / Ultra PTZ Wall MountShort 11"
RHOLW	illustra / Ultra PTZ Wall Mount Long 23"
RHOTR	illustra / Ultra PTZ Over Roof Mount
ROTRF	Floor Adapter for RHOTR PTZ mount
RHOWCA	PTZ Corner adaptor, used with RHOxW
ROENDC	End Cap for RHOxW, Spare
IPTZPOEBT60	illustra Flex IR 30x PTZ, 1PORT BT INJECTOR 60W
ADSPOT	Power Supply, 1 O/P, 120/240V to 24V, NEMA 4



About Johnson Controls

Johnson Controls is a global diversified technology and multi-industrial leader serving a wide range of customers in more than 150 countries. Our 120,000 employees create intelligent buildings, efficient energy solutions, integrated infrastructure and next generation transportation systems that work seamlessly together to deliver on the promise of smart cities and communities. Our commitment to sustainability dates back to our roots in 1885, with the invention of the first electric room thermostat.

For additional information, please visit www.illustraceras.com or follow us on Facebook, Twitter, and LinkedIn.